

Furniture & Office Casters

Roulettes pour meubles et bureaux



F46078



F48105



F48061



F48364



F31551

FEATURES AND APPLICATIONS

- **Soft, non-marking tread casters** ideal for hard surfaces, such as hardwood, tile, linoleum, and ceramic. Polyurethane (PU) for scratch-free, noise-reducing protection (TPU for F24810).
- Friction grip stem standard for most office chairs (5 casters)

CARACTÉRISTIQUES ET APPLICATIONS

- **Roulettes à bande de roulement douce** qui ne marquent pas les planchers, idéales sur planchers de bois franc, tuile, linoléum et céramique. Bande en polyuréthane (PU) qui protège contre les égratignures et réduisent les bruits déplaisants (TPU pour F24810).
- Tige à serrage de friction standard pour la plupart des chaises de bureau à 5 roulettes

Dual-Wheel: Soft Tread • Jumelée : bande de roulement douce

No.	MOUNTING FIXATION	BRAKE FREIN			COLOUR COULEUR	TOTAL HEIGHT HAUTEUR TOTALE	No.	PACKAGING EMBALLAGE	QTY QTÉ
★ F46078	Friction grip stem Tige à serrage de friction 1	✗	2" / 50 mm	110 lb / 50 kg	Black-Grey / Noir-gris	2-3/8" / 61 mm	-		
★ F46043	Threaded stem / Tige filetée 5/16"-18 x 1"	✗	2" / 50 mm	110 lb / 50 kg	Black-Grey / Noir-gris	2-3/8" / 61 mm	-		
★ F46143	Wood stem / Tige à bois	✗	2" / 50 mm	110 lb / 50 kg	Black-Grey / Noir-gris	2-5/16" / 59 mm	-		
★ F46144	Plate / Plaque	✗	2" / 50 mm	110 lb / 50 kg	Black-Grey / Noir-gris	2-1/2" / 64 mm	-		
F24810	Friction grip stem Tige à serrage de friction 1	✗	2-3/8" / 60 mm	66 lb / 30 kg	Black / Noir	2-23/32" / 69 mm	-		

Dual-Wheel • Jumelée

No.	MOUNTING FIXATION	BRAKE FREIN			COLOUR COULEUR	TOTAL HEIGHT HAUTEUR TOTALE	No.	PACKAGING EMBALLAGE	QTY QTÉ
F48104	Wood stem / Tige à bois	✗	1-9/16" / 40 mm	55 lb / 25 kg	Black / Noir	2" / 50 mm	-		
F48105	Wood stem / Tige à bois	✓	1-9/16" / 40 mm	55 lb / 25 kg	Black / Noir	2" / 50 mm	-		
F48106	Plate / Plaque	✗	1-9/16" / 40 mm	55 lb / 25 kg	Black / Noir	2-5/32" / 55 mm	-		
F48107	Plate / Plaque	✓	1-9/16" / 40 mm	55 lb / 25 kg	Black / Noir	2-5/32" / 55 mm	-		
F48359	U-bracket / Fixation en U	✗	1-9/16" / 40 mm	55 lb / 25 kg	Black / Noir	2-7/32" / 56 mm	-		
F46180	Friction grip stem Tige à serrage de friction 1	✗	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-3/8" / 60 mm	F22815	Clamshell	2
F48061	Threaded stem / Tige filetée 5/16"-18 x 1"	✗	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-7/16" / 62 mm	-		
F24812	Wood stem / Tige à bois	✗	2" / 50 mm	77 lb / 35 kg	White / Blanc	2-3/8" / 60 mm	-		
F48425	Wood stem / Tige à bois	✗	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-3/8" / 60 mm	-		
F31744	Wood stem / Tige à bois	✓	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-3/8" / 60 mm	-		
F24811	Plate / Plaque	✗	2" / 50 mm	77 lb / 35 kg	White / Blanc	2-19/32" / 66 mm	-		
F48039	Plate / Plaque	✗	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-19/32" / 66 mm	-		
F45497	Plate / Plaque	✓	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-19/32" / 66 mm	-		
F48363	U-bracket / Fixation en U	✗	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-19/32" / 66 mm	-		
F48364	U-bracket / Fixation en U	✓	2" / 50 mm	66 lb / 30 kg	Black / Noir	2-19/32" / 66 mm	-		

¹ Diameter 7/16" x Length 27/32" / Diamètre de 11 mm x longueur de 21.6 mm

Metal Ball • Sphérique en métal

No.	MOUNTING FIXATION			FINISH FINI	TREAD WIDTH LARGEUR DE BANDE	TOTAL HEIGHT HAUTEUR TOTALE	No.	PACKAGING EMBALLAGE	QTY QTÉ
F31551	Plate / Plaque	2-1/8" / 55 mm	75 lb / 34 kg	Brass / Laiton	7/16" / 11 mm	2-15/32" / 62.5 mm	-		